© EPODOC / EPO

EP0371858 A 19900606 PN

1990-06-06 PD

PR FR19880015589 19881129

OPD - 1988-11-29

AB

- Individual respiratory and contamined environment protective equipment. ΤI

- The individual equipment makes it possible particularly to protect the members of the crew of fighter aircraft against the effect of high altitude and NBC contamination. It comprises a respiratory mask (18) equipped with a pipe (35, 36) for connection to an external respiratory gas source, a helmet having a rigid shell (10) and a detachable padding (12), and a hood (20) equipped with a visor. The padding (12) and the shell (10) are provided so that they can to one another either directly or by means of the hood (20). The hood is equipped with means (48) for the sealed passage of the pipe (35) for connection to the mask.

<IMAGE>

 BEAUSSANT RAYMOND IN

- INTERTECHNIQUE SA (FR) PA

- A42B3/10 ; A42B3/12 ; A42B3/28 ; A62B17/04 ; A62B18/04 EC

- A42B3/10 ; A62B17/04 IC

- US4266301 A [A]; FR2350851 A [A]; US2390233 A [A]; CT FR1493964 A [A]

GB800600 A [A];

O WPI / DERWENT

- Protective helinet and breathing apparatus set has removable internal padding and intermediate ΤI flexible hood associated with rigid helmet shell and respiratory mask
- FR19880015589 19881129 PR
- EP0371858 A 19900606 DW199023 000pp PN
 - FR2639545 A 19900601 DW199029 000pp
 - EP0371858 B1 19921216 DW199251 A62B17/04 Fm 007pp
 - DE68903934E E 19930128 DW199305 A62B17/04 000pp
- (SEAL) INTERTECHNIQUE SA PA
- A42B3/10 ;A62B17/04 ;A62B18/00 IC
- IN - BEAUSSANT R
- EP-371858 The apparatus consists of a respiratory mask (18) covering the wearer's mouth and AB nose, with a delivery conduit (35) for connection to an external source of breathable gas. A helmet with a rigid shell (10) and removable internal padding (12) is associated with a hood (20) including a visor and ventilation openings. The padding its into the helmet shell with or without the intermediate inclusion of the hood. The hood includes a sealable opening (48) for passage of the breathing conduit, and has holes for passage of fasteners securing the padding to the interior of the helmet. USE - Protection of wearer against nuclear, biological or chemical contamination. (7pp Dwg.No.1/4)
- EPAB EP-371858 An individual breathing and protective apparatus in a contaminated environment, comprising a breathing mask (18) for nose and mouth, itted with a duct (35) for connecting to an external source of respiratory gas, a neimet having a rigid shell (10) and detachable padding (12), and a nood (20) with a visor, together with means for supplying air for ventilation, characterised in that the padding (12) and the shell (10) are adapted to it in one another, either directly or via the hood (20) inserted between them, and the hood (20) has sealing-tight lead-in means (48) for the connecting duct (35).
 - (Dwg.1/5)
- OPD 1988-11-29
- FR1493964;FR2350851;GB800600;US2390233;US4266301

DS - DE ES GB IT AN - 1990-173199 [23]